



OUTLET BODIES WITH MOUNTING FLANGE



GECXTF
XTF Type Outlet Body
With Mounting Flange



GECUET-2
Outlet Body



GEUEAT-2
Outlet Body

1/2", 3/4" and 1" Bodies
Class I, Div. 1 & 2, Groups B, C,
D Class I, Zone 1, Groups IIB,
IIA Class II, Div. 1 & 2, Groups
E, F, G Class III
TYPE 4, 4X

 LISTED E 10514

 LR11716

Applicable Third Party Standards

UL Standards: 886 and 1203

CSA Standard: C22.2 No. 30

Fed Spec: W-C-586D

Mil Spec: F-28675

FEATURES-SPECIFICATIONS

Materials

Aluminum

- **BODY** Copper-free aluminum (less than 1/100 of 1%)
- **FINISH** Electrostatically applied powder coating
- **COVER** (Aluminum) Copper-free aluminum (less than 1/100 of 1%). Electrostatically applied powder coating

Iron

- **BODY** Duraloy iron alloy
- **FINISH** Tri-Coat Finish of Electrocoat, Chromate Sealant, and electrostatically applied powder coating
- **COVER** (Aluminum) Copper-free aluminum (less than 1/100 of 1%). Electrostatically applied powder coating

Size Ranges:

- Hub – 3/4" standard
» optional 1/2" to 1" contact factory
- Cover opening – 2-11/16" or 2-1/16"