

PLM • Fittings For Metal Clad Cable

FEATURES/BENEFITS

- Slip-on design with no disassembly for easy installation.
- Neoprene bushing for raintight seal.
- Locknuts, bushings and flange gasket included - no additional materials to purchase.
- Flange gasket prevents moisture penetration through threads.
- Made from copper-free aluminum alloy for corrosion resistance.
- Fits broad range - .351-4.62 cable O.D.

APPLICATION

- For terminating metal clad cable

CERTIFICATION



TO ORDER

DETERMINE SATISFACTORY FIT BY CHECKING CABLE DIMENSIONS A AND B. IF CABLE DIMENSIONS DO NOT FALL WITHIN ACCEPTABLE RANGE, CONSULT FACTORY.

Catalog Number Ship Wt.	A Dia. Over Jacket		B Core Dia.	C Max. Cable Size	D Conduit O.D.	E Fitting Overall	Length (Lbs.)
JAG 45-0S	.35	.45	.61	1/2	1-5/8	2-1/4	1/4
JAG 55-0S	.45	.55	.61	1/2	1-5/8	2-1/4	1/4
JAG 65-0S	.55	.65	.61	1/2	1-5/8	2-1/4	1/4
JAG 75-0S	.65	.75	.61	1/2	1-5/8	2-1/4	1/4
JAG 85-0S	.75	.85	.61	1/2	1-5/8	2-1/4	1/4
JAG 95-0S	.85	.95	.61	1/2	1-5/8	2-1/4	1/4
JAG 99-07	.85	.99	.81	3/4	2	2-5/8	1/3
JAG 107-07	.92	1.07	.81	3/4	2	2-1/4	1/3
JAG 113-07	.98	1.13	.81	3/4	2	2-1/4	1/3
JAG 121-07	1.07	1.21	.81	3/4	2	2-1/4	1/3
JAG 112-10	1.00	1.12	1.00	1	2-3/8	3-1/16	1/2
JAG 125-10	1.12	1.25	1.00	1	2-3/8	3-1/16	1/2
JAG 138-10	1.22	1.38	1.00	1	2-3/8	3-1/16	1/2
JAG 138-12	1.28	1.38	1.25	1-1/4	2-7/8	3-3/8	2/3
JAG 156-12	1.38	1.56	1.25	1-1/4	2-7/8	3-3/8	2/3
JAG 174-12	1.56	1.74	1.25	1-1/4	2-7/8	3-3/8	2/3
JAG 188-12	1.74	1.88	1.25	1-1/4	2-7/8	3-3/8	2/3
JA6 174-15	1.60	1.74	1.63	1-1/2	3-1/4	4-1/16	1
JAG 188-15	1.74	1.88	1.63	1-1/2	3-1/4	4-1/16	1
JAG 200-15	1.88	2.00	1.63	1-1/2	3-1/4	4-1/16	1
JAG 218-15	2.00	2.18	1.63	1-1/2	3-1/4	4-1/16	1
JAG 219-20	2.05	2.19	2.09	2	4	4-5/16	1-1/2
JAG 236-20	2.19	2.36	2.09	2	4	4-5/16	1-1/2
JAG 247-20	2.35	2.47	2.09	2	4	4-5/16	1-1/2
JAG 261-20	2.47	2.61	2.09	2	4	4-5/16	1-1/2
JAG 263-25	2.46	2.63	2.49	2-1/2	4-23/32	5-7/16	2-1/2
JAG 280-25	2.62	2.80	2.49	2-1/2	4-23/32	5-7/16	2-1/2
JAG 296-25	2.80	2.96	2~49	2-1/2	4-23/32	5-7/16	2-1/2
JAG 297-30	2.80	2.97	3.11	3	5-3/32	5-3/4	3
JAG 311-30	2.95	3.11	3.11	3	5-3/32	5-3/4	3
JAG 327-30	3.10	3.27	3.11	3	5-3/32	5-3/4	3
JAG 343-30	3.26	3.43	3.11	3	5-3/32	5-3/4	3
JAG 359-30	3.42	3.59	3.11	3	5-3/32	5-3/4	3
JAG 375-35	3.52	3.75	3.61	3-1/2	5-11/16	5-13/16	3-1/4
JAG 392-35	3.75	3.92	3.61	3-1/2	5-11/16	5-13/16	3-1/4
JAG 412-35	3.90	4.12	3.61	3-1/2	5-11/16	5-13/16	3-1/4
JAG 423-40	4.05	4.23	4.11	4	6-3/32	5-13/16	3-1/2
JAG 437-40	4.20	4.37	4.11	4	6-3/32	5-13/16	3-1/2
JAG 4S1-4B	4.34	4.51	4.11	4	6-3/32	5-13/16	3-1/2
JAG 462-40	4.43	4.62	4.11	4	6-3/32	5-13/16	3-1/2